



Diva redefines standards in the industry of patio doors. Its renewed appearance is combined to unequalled perforance with respect to energy efficiency, solidity and security. The Diva patio door confirms the creators' commitment to make it an uncompromisingly superior product for either new construction or renovation projects.

Standard Features

- The Diva patio door has a 4 5/8" all PVC frame with integral nailing fin.
- The Diva patio door is offered standard with multipoint lock for added security.
- The screen can also be locked from the inside.
- Sloped sill for optimal water drainage.
- The Diva patio door is suitable for new construction or remodeling.
- All sashes are fusion welded for more strength.
- Fully reversible can be assembled to slide left or right.
- The opening sash integrates double tandem adjustable rollers for smooth and easy operation on anodized aluminum tracks.

Warranty

Every Diva patio door is delivered with a limited warranty:

20-year on PVC.

10-year against seal failure.

Diva is a creation of



Collaboration in Action

Options

The Diva patio door comes with a complete line of options to suit individual requirements.

- Lock and key.
- Security bar.
- Many glazing options: Low E (Argon), tinted, with or without grills.

Don Young Co. Windows & Doors

(214) 630-0934 **Dallas** (713) 868-1398 Houston (210) 225-0352 San Antonio Lubbock (806) 747-2181 (405) 947-2000 Oklahoma City

www.dycwindows.com

Sturdiness

- The Diva patio door uses heavy duty aluminum extrusions for screen.
- The vertical stiles are reinforced with metal.
- The sill is made of reinforced PVC for greater resistance.
- The Diva patio door is built with multichamber heavy duty PVC profiles for maximum strength and rigidity.

Performance

- Full perimeter weatherstrip forms a positive seal between frame and panels.
- Multichamber insulating PVC profiles to provide maximum comfort.
- Strong interlocking meeting rail for air tightness.

US Standards

- Meets the AAMA/NWWDA 101/1.S.2-97
- SGD-R50 (72 x 80)
- NFRC tested
- HUD certified TDI qualified

Canadian Standards

- Meets CSA-A440
- Air tightness:
- Water Resistance: B4 · Wind load resistance: C2
- · Ease of operation: • Forced entry:
- Energy rating (LowE + Argon): -1

Sizes Available

I	Nominal size	Туре	Frame size	Recommanded Rough opening
	5'0" x 6'8"	OX or XO	59 1/4" x 79 1/2"	60" x 80"
	6'0" x 6'8"	OX or XO	71 1/4" x 79 1/2"	72" x 80"
	8'0" x 6'8"	OX or XO	95 1/4" _x 79 1/2"	96" x 80"
	9'0" x 6'8"	OXO*	107 3/4" _x 79 1/2"	108 1/2" x 80"
	12'0" x 6'8"	OXO*	143 3/4" _x 79 1/2"	144 1/2" x 80"

* 9' and 12' units are constitued of a standard 6' or 8' door mulled to a sidelite





Our Customers Assemble Energy-Efficient adows and Doors with Thermoplast Vinyl Profiles

Custom sizes available upon request.